
## Karakteristikler



- Her tür döner kap?ya kurulmak için tasarlanm??t?r. Mümkün iki pozisyonlu, ?smarlama boyutlarla.
- Çinko kaplama çelik levhadan yap?lm?? kendini ta??yan kasa yap?s?, standart olarak yap?sal epoksi-polyester RAL9016 beyaz boyayla cilalan?r.Paslanmaz çelik veya di?er renkler iste?e tabiidir.
- A??r? bak?m gerektirmeyen büyük fasetli hava giri?i ?zgaras?.
- Dairesel anodize edilmi? alüminyum ç?k?? pervaneleri, kanat ?eklinde.
- Dü?ük ses seviyeli ve d??tan rotor motorlar?yla hareket eden çift giri?li santrüfüj motorlar?. 5-h?z seviyeli.EC modelleri dü?ük tüketimli verimli fanlar içerir.
- "P" tipi su ile ?s?t?lan bobin."E" tipi elektrik korumal? elementler, birle?ik ayarl? üç evre."A" tipi ?s?tmas?z, sadece hava ile.?ste?e ba?l? geni?leme DX bobin
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  • Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  • Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

## Ki?iselle?tirme

50Hz

| Model | Is?nmam?? | |
|---|---|---|
| | (m³/h) | (m) |
| ROTO BB 1000 A | 5-7 | |
| ROTO BB 1500 A | 5-7 | |
| ROTO BB 2000 A | 5-7 | |
| ROTO BB 2500 A | 5-7 | |
| ROTO SB 1000 A | 3,5-5 | |
| ROTO SB 1500 A | 3,5-5 | |
| ROTO SB 2000 A | 3,5-5 | |
| ROTO SB 2500 A | 3,5-5 | |

| Model | Elektrikli Is?tma | | | |
|---|---|---|---|---|
| | (m³/h) | (kW) | (m) | (kW) |
| ROTO BB 1000 E | - | | | |
| ROTO BB 1500 E | - | | | |
| ROTO BB 2000 E | - | | | |
| ROTO BB 2500 E | - | | | |
| ROTO SB 1000 E | 12,44 | | | |
| ROTO SB 1500 E | - | | | |
| ROTO SB 2000 E | - | | | |
| ROTO SB 2500 E | - | | | |

| Model | Su Is?tma | | | | |
|---|---|---|---|---|---|
| | (m³/h) | (m) | (kW) | (kW) | (kW) |
| ROTO BB 1000 P86 | - | | | | |
| ROTO BB 1500 P86 | - | | | | |

| Model | Su Is?tma (m³/h) | (m) | (kW) | (kW) | (kW) |
|---|---|---|---|---|---|
| ROTO BB 2000 P86 | - | | | | |
| ROTO BB 2500 P86 | - | | | | |
| ROTO SB 1000 P86 | - | | | | |
| ROTO SB 1500 P86 | - | | | | |
| ROTO SB 2000 P86 | - | | | | |
| ROTO SB 2500 P86 | - | | | | |
| ROTO BB 1000 P64 | - | | | | |
| ROTO BB 1500 P64 | - | | | | |
| ROTO BB 2000 P64 | - | | | | |
| ROTO BB 2500 P64 | - | | | | |
| ROTO SB 1000 P64 | - | | | | |
| ROTO SB 1500 P64 | - | | | | |
| ROTO SB 2000 P64 | - | | | | |
| ROTO SB 2500 P64 | - | | | | |
| ROTO BB 1000 P54 | 36.57 | | | | |
| ROTO BB 1500 P54 | 15.16 | | | | |
| ROTO BB 2000 P54 | 38.96 | | | | |
| ROTO BB 2500 P54 | 24.15 | | | | |
| ROTO SB 1000 P54 | 14,47 | | | | |
| ROTO SB 1500 P54 | 21,19 | | | | |
| ROTO SB 2000 P54 | 30,77 | | | | |
| ROTO SB 2500 P54 | 36,94 | | | | |

60Hz

| Model | Is?nmam?? (m³/h) | (m) |
|---|---|---|
| ROTO BB 1000 A | 5-7 | |
| ROTO BB 1500 A | 5-7 | |
| ROTO BB 2000 A | 5-7 | |
| ROTO BB 2500 A | 5-7 | |

| Model | Elektrikli Is?tma (m³/h) | (kW) | (m) | (kW) |
|---|---|---|---|---|
| ROTO BB 1000 E | - | | | |
| ROTO BB 1500 E | - | | | |
| ROTO BB 2000 E | - | | | |
| ROTO BB 2500 E | - | | | |

| Model | Su Is?tma (m³/h) | (m) | (kW) | (kW) | (kW) |
|---|---|---|---|---|---|
| ROTO BB 1000 P86 | - | | | | |
| ROTO BB 1500 P86 | - | | | | |
| ROTO BB 2000 P86 | - | | | | |
| ROTO BB 2500 P86 | - | | | | |
| ROTO BB 1000 P64 | - | | | | |
| ROTO BB 1500 P64 | - | | | | |

| Model | Su Is?tma | | | | |
|---|---|---|---|---|---|
| | (m³/h) | (m) | (kW) | (kW) | (kW) |
| ROTO BB 2000 P64 | - | | | | |
| ROTO BB 2500 P64 | - | | | | |
| ROTO BB 1000 P54 | 36.57 | | | | |
| ROTO BB 1500 P54 | 15.16 | | | | |
| ROTO BB 2000 P54 | 38.96 | | | | |
| ROTO BB 2500 P54 | 24.15 | | | | |

## Boyutlar

