


## Karakteristikler



- Her tür döner kap?ya kurulmak için tasarlanm??t?r. M?mk?n iki pozisyonlu, ?sma?lama boyutlarla.
- Çinko kaplama çelik levhadan yap?lm?? kendini ta??yan kasa yap?s?, standart olarak yap?sal epoksi-polyester RAL9016 beyaz boyayla cilalan?r.Paslanmaz çelik veya di?er renkler iste?e tabiidir.
- A??r? bak?m gerektirmeyen büyük fasetli hava giri?i ?zgaras?.
- Dairesel anodize edilmi? alüminyum ç?k?? pervaneleri, kanat ?eklinde.
- D?ük ses seviyeli ve d??tan rotor motorlar?yla hareket eden çift giri?li santrüf?j motorlar?. 5-h?z seviyeli.EC modelleri dü?ük tüketimli verimli fanlar içerir.
- "P" tipi su ile ?s?t?lan bobin."E" tipi elektrik korumal? elementler, birle?ik ayarl? uç evre."A" tipi ?s?tmas?z, sadece hava ile ?ste?e ba?l? geni?leme DX bobin
- Advanced Plug&Play kontrol. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

## Ki?iselle?tirme

50Hz

### Is?nma??

Model	(m <sup>3</sup> /h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	
ROTO SB 1000 A	3,5-5	
ROTO SB 1500 A	3,5-5	
ROTO SB 2000 A	3,5-5	
ROTO SB 2500 A	3,5-5	

### Elektrikli Is?tma

Model	(m <sup>3</sup> /h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			
ROTO SB 1000 E	12,44			
ROTO SB 1500 E	-			
ROTO SB 2000 E	-			
ROTO SB 2500 E	-			

### Su Is?tma

Model	(m <sup>3</sup> /h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				



Su Is?tma					
Model	(m <sup>3</sup> /h)	(m)	(kW)	(kW)	(kW)
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO SB 1000 P86	-				
ROTO SB 1500 P86	-				
ROTO SB 2000 P86	-				
ROTO SB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO SB 1000 P64	-				
ROTO SB 1500 P64	-				
ROTO SB 2000 P64	-				
ROTO SB 2500 P64	-				
ROTO BB 1000 P54	36,57				
ROTO BB 1500 P54	15,16				
ROTO BB 2000 P54	38,96				
ROTO BB 2500 P54	24,15				
ROTO SB 1000 P54	14,47				
ROTO SB 1500 P54	21,19				
ROTO SB 2000 P54	30,77				
ROTO SB 2500 P54	36,94				

60Hz

Is?nmam??		
Model	(m <sup>3</sup> /h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	

Elektrikli Is?tma				
Model	(m <sup>3</sup> /h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			

Su Is?tma					
Model	(m <sup>3</sup> /h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				

Su Is?tma

Model	(m <sup>3</sup> /h)	(m)	(kW)	(kW)	(kW)
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO BB 1000 P54	36.57				
ROTO BB 1500 P54	15.16				
ROTO BB 2000 P54	38.96				
ROTO BB 2500 P54	24.15				

Boyutlar

